



Product information

Erem®

1522N

Code No. : **T1522N**

Cutting head for 1500 BSF - side cutter - oval head

- This is the standard head shape.
- It is used for all cutting jobs in easy-to-reach areas.
- The oval head provides for a high cutting capacity and is characterised by its robustness.

Technical Data

| | |
|---------------------------------|----------------------|
| Cut: | Flush |
| Weight: | 35 g / 1.16 oz. |
| Length of cutting edges: | 10 mm / .394 Inch |
| Head width: | 10,5 mm / .413 Inch |
| Head thickness: | 6,5 mm / .256 Inch |
| Max. cutting capability | |
| Copper wire: | Ø 1,6 mm / .062 Inch |

Erem Cutters and Tip Cutters

- Internal patented Erem Magic Spring

- Reduce costs by long life
- Constant spring force
- Guarantees more than 1 million operations
- High precision screw joint
 - Smooth jaw action with no play
 - Smooth cutting operation with no jaw overlapping
- Induction-hardened cutting edges in Rockwell hardness 63 - 65 HRc for exceptionally long life
- EMOS maximum opening stop
 - limits the cutting-edge tips from opening more than 5 mm / .197 Inch. The limited extent to which the handles can open prevent user hand fatigue.
- Ergonomically shaped handles
 - for high comfort, better grip and added safety
- Erem cut:
 - Options for semi flush, full flush or super flush cuts