



RECOMMENDED PC BOARD LAYOUT

- 1 HOUSING MATERIAL: GLASS FILLED POLYESTER, COLOR- BLACK
- 2 CONTACT MATERIAL: PHOSPHOR BRONZE
- 3 CONTACT FINISH: 0.00076[.000030] THK DUPLEX PLATED GOLD ON CONTACT AREA, 0.00127[.000050] MIN THK BRIGHT TIN-LEAD ON SOLDERLEADS, ALL OVER 0.00127[.000050] NICKEL
- 4 MOLDED IN ARROW DESIGNATES THE MATING FACE OF THE CONNECTOR
- 5 POINT OF MEASUREMENT FOR PLATING THICKNESS OF CONTACT AREA
- 6 DIMENSIONS PERTAIN TO HOUSING CAVITY CENTERLINES
- 7 PART NUMBER AND DATE CODE MARKED IN APPROXIMATE LOCATION SHOWN, EITHER END.
- 8 ALTERNATE LOCATION FOR DATE CODE FOR 4 AND 6 POSITION.
- 9 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI
- 10 TE LOGO AND CSA LOGO ARE MOLDED INTO HOUSING, THIS LOCATION.

	10.16 [.400]	12.70 [.500]	10	6-535512-4
	7.62 [.300]	10.16 [.400]	8	6-535512-3
	5.08 [.200]	7.62 [.300]	6	6-535512-2
	2.54 [.100]	5.08 [.200]	4	6-535512-1
9	162.56 [6.400]	165.10 [6.500]	130	6-535512-0
	160.02 [6.300]	162.56 [6.400]	128	5-535512-9
	157.48 [6.200]	160.02 [6.300]	126	5-535512-8
	152.40 [6.000]	154.94 [6.100]	122	5-535512-7
	149.86 [5.900]	152.40 [6.000]	120	5-535512-6
9	147.32 [5.800]	149.86 [5.900]	118	5-535512-5
	144.78 [5.700]	147.32 [5.800]	116	5-535512-4
9	142.24 [5.600]	144.78 [5.700]	114	5-535512-3
	139.70 [5.500]	142.24 [5.600]	112	5-535512-2
9	137.16 [5.400]	139.70 [5.500]	110	5-535512-1
	134.62 [5.300]	137.16 [5.400]	108	5-535512-0
	132.08 [5.200]	134.62 [5.300]	106	4-535512-9
	129.54 [5.100]	132.08 [5.200]	104	4-535512-8
	127.00 [5.000]	129.54 [5.100]	102	4-535512-7
9	124.46 [4.900]	127.00 [5.000]	100	4-535512-6
	121.92 [4.800]	124.46 [4.900]	98	4-535512-5
	119.38 [4.700]	121.92 [4.800]	96	4-535512-4
	116.84 [4.600]	119.38 [4.700]	94	4-535512-3
	114.30 [4.500]	116.84 [4.600]	92	4-535512-2
	111.76 [4.400]	114.30 [4.500]	90	4-535512-1
9	109.22 [4.300]	111.76 [4.400]	88	4-535512-0
	106.68 [4.200]	109.22 [4.300]	86	3-535512-9
	104.14 [4.100]	106.68 [4.200]	84	3-535512-8
	101.60 [4.000]	104.14 [4.100]	82	3-535512-7
9	99.06 [3.900]	101.60 [4.000]	80	3-535512-6
	96.52 [3.800]	99.06 [3.900]	78	3-535512-5
	93.98 [3.700]	96.52 [3.800]	76	3-535512-4
	91.44 [3.600]	93.98 [3.700]	74	3-535512-3
9	88.90 [3.500]	91.44 [3.600]	72	3-535512-2
	86.36 [3.400]	88.90 [3.500]	70	3-535512-1
	83.82 [3.300]	86.36 [3.400]	68	3-535512-0
	81.28 [3.200]	83.82 [3.300]	66	3-535512-9
	78.74 [3.100]	81.28 [3.200]	64	3-535512-8
9	76.20 [3.000]	78.74 [3.100]	62	3-535512-7
	73.66 [2.900]	76.20 [3.000]	60	3-535512-6
	71.12 [2.800]	73.66 [2.900]	58	3-535512-5
	68.58 [2.700]	71.12 [2.800]	56	3-535512-4
	66.04 [2.600]	68.58 [2.700]	54	3-535512-3
	63.50 [2.500]	66.04 [2.600]	52	3-535512-2
	60.96 [2.400]	63.50 [2.500]	50	3-535512-1
	58.42 [2.300]	60.96 [2.400]	48	3-535512-0
	55.88 [2.200]	58.42 [2.300]	46	2-535512-9
	53.34 [2.100]	55.88 [2.200]	44	2-535512-8
	50.80 [2.000]	53.34 [2.100]	42	2-535512-7
	48.26 [1.900]	50.80 [2.000]	40	2-535512-6
	45.72 [1.800]	48.26 [1.900]	38	2-535512-5
	43.18 [1.700]	45.72 [1.800]	36	2-535512-4
	40.64 [1.600]	43.18 [1.700]	34	2-535512-3
	38.10 [1.500]	40.64 [1.600]	32	2-535512-2
	35.56 [1.400]	38.10 [1.500]	30	2-535512-1
	33.02 [1.300]	35.56 [1.400]	28	2-535512-0
	30.48 [1.200]	33.02 [1.300]	26	2-535512-9
	27.94 [1.100]	30.48 [1.200]	24	2-535512-8
	25.40 [1.000]	27.94 [1.100]	22	2-535512-7
	22.86 [900]	25.40 [1.000]	20	2-535512-6
	20.32 [800]	22.86 [900]	18	2-535512-5
	17.78 [700]	20.32 [800]	16	2-535512-4
	15.24 [600]	17.78 [700]	14	2-535512-3
	12.70 [500]	15.24 [600]	12	2-535512-2
	10.16 [400]	12.70 [500]	10	2-535512-1
	7.62 [300]	10.16 [400]	8	2-535512-0
	5.08 [200]	7.62 [300]	6	1-535512-9
	2.54 [100]	5.08 [200]	4	1-535512-8
				1-535512-7
				1-535512-6
				1-535512-5
				1-535512-4
				1-535512-3
				1-535512-2
				1-535512-1
				1-535512-0
				0-535512-9
				0-535512-8
				0-535512-7
				0-535512-6
				0-535512-5
				0-535512-4
				0-535512-3
				0-535512-2
				0-535512-1
				0-535512-0

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN R BROWN 17MAY02	TE Connectivity
0 PLC ± -	1 PLC ± -	CHK J OLSON 17MAY02	AMPMODU MOD II RECEPTACLE ASSEMBLY, HORIZONTAL, .100 CL, 2 ROW, CLOSED-ENTRY, SHORT POINT OF CONTACT, END-TO-END STACKABLE
2 PLC ± -	3 PLC ± 0.13 [.005]	APVO J OLSON 17MAY02	NAME
4 PLC ± -	ANGLES ± -	PRODUCT SPEC	SIZE CASE CODE DRAWING NO
MATERIAL	FINISH	APPLICATION SPEC	WEIGHT
		SIZE	A1 00779 535512
		RESTRICTED TO	CUSTOMER DRAWING

SCALE 5:1 SHEET 1 OF 1 REV Y5