

Data sheet Product LA ICK PEN 16 W 12




Heatsinks and active heatsinks for processors>Active heatsinks for processors
for Intel Pentium and MMX

Features

way of fixation:	therm. cond. adhesive
socket:	• socket 7 • socket 370
thermal resistance:	1.2 K/W
suitable for processor type:	• AMD® K6-III • IDT W2A • Cyrix MII and similar • MMX • IDT C6 • Intel® Pentium® • AMD® K6-2
dissipation loss:	51.1 W
operating voltage of the fan motor:	12 V
surface:	black anodised

Technical Drawing



A:	50.8 mm
B:	50.8 mm
C:	16.51 mm

D:	26.51 mm
----	----------

Fan

circuit voltage:	12 V DC
bearing type:	ball bearing
fan dimensions:	50x50x10 mm
cur. consumpt.:	50 mA
max. iuitial current:	140 mA
max. volume flow:	238 l/min 14.3 m ³ /h
max. static pressure:	3.0mm H ₂ O 29.6 Pa
noise level:	27 dB(A), 1 m frontal
temperature range:	-40°C... +85°C
failure rate (L ₁₀):	40.000 h (40°C)
MTBF:	350.000 h (40°C)
weight:	19 g
cases:	plastic PBT (UL E54695)