

Data sheet Product SL 11 SMD 104 34 G B SM



PCB connectors>Male headers

□ 0.635 mm

... packing (option) - additions:

SL 11 SMD 040-104 ... SM; ... B SM: 6-40 contacts

SL 11 SMD 040-062 ... B TR: 26-40 contacts, 250 pcs/reel

SL 11 SMD 040-078 ... B TR: 6-24 contacts, **250 pcs/reel**

SL 11 SMD 104-130 ... B TR: 6-24 **contacts**, 150 pcs/reel

Features

pitch: 2.54 x 2.54 mm

no. of contacts: 34

contact material: CuSn-alloy

surface of contact: gold-plated

surface contact /
contact sleeve:

- Ni+≥0.2µm Au
- Ni+4...6µm Sn

version: male header

volume resistance: ≤5 mΩ

nominal current: 3 A

nominal voltage: 250 V AC

test voltage: 2000 V

insulating body material: PA 4.6. GF

temperature range:

- -40°C... +163°C
- (260°C/10 s)

class of inflammability: UL 94 V-0

specific insulation
resistance: >10⁷ Ω·m




connection type: SMD

reflow solderable: yes

packing (optional):

pick and place pad and bar magazine


Technical Drawing







C: 10.8 mm

S: 5.0 mm

Equipping



... SM
... B SM




SL 11 SMD ... SM


SL 11 SMD ... B SM




... B TR




SL 11 SMD 040-062 ... 6-24 ... B TR



SL 11 SMD 040-062 ... 26-40 ... B TR



SL 11 SMD 078 ... B TR



SL 11 SMD 104-130 ... 6-24 ... B TR

Fischer Elektronik GmbH & Co. KG
DEUTSCHLAND • GERMANY • ALLEMAGNE

Nottebohmstraße 28
58511 Lüdenscheid

Telefon +49 2351 435-0
Telefax +49 2351 45754

info@fischerelektronik.de
www.fischerelektronik.de