


Item no.: 734-312/019-000
 Product description: MALE CONNECTOR WITH FIXING FLANGE 12 POLE PIN SPACING 3.5 MM / 0.138 IN 100% PROTECTED AGAINST MISMATING FOR SCREW OR SIMILAR MOUNTING TYPES FOR PARALLEL OR PERPENDICULAR MOUNTING



Produkt kann von Bild abweichen / product may differ

Packing unit 25 pieces

RoHS compliant

Product group	3 (Multi Conn. System)
Weight	10.952 g
Color	light gray
No. of connection Points	12
No. of potentials	12
pole count	12
Height	13.4 mm
Height	0.528 in
Width	56.8 mm
Width	2.236 in
Depth	22.3 mm
Depth	0.878 in
Pin spacing from	3.5 mm
Pin spacing from	0.138 in
Pollution degree	2
Measured voltage EN	160 V
Measured shock voltage	2.5 kV

Current intensity EN	10 A
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	2.5 kV
Current intensity EN	10 A



Connection method	CAGE CLAMP® CONNECTION
Cross section [mm ²]	0.08 - 1.5 mm ²
Wiring method	solid
Cross section [mm ²]	0.08 - 1.5 mm ²
Cross section [mm ²]	0.25 - 1.5 mm ²
Cross section [mm ²]	0.25 - 1.5 mm ²
Cross section [AWG]	28 - 14 AWG
Strip length from	6 mm
Strip length to	7 mm
Material group	I
xxx-xxx/034-000	Strain relief plate 25 mm



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
734-312/019-000	ABS	04-HG469925/1-PDA	250	10	0,5-1,5
734-312/019-000	CCA	NL5641	250	10	0,5-1,5
734-312/019-000	CSA	154112-1465035	300	10	28-14
734-312/019-000	KEMA	2077592.02	250	10	0,5-1,5
734-312/019-000	UR	E45171	250	10	28-14
734-312/019-000	UR	E45172	300	10	28-14

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected