

## FO CA PP2-SCdx, 62,5µ, OM1, PUR, 30m



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                     |
|--------------------|-------------------------------------------------------------------------------------|
| Part number        | 33 61 431 0300 006                                                                  |
| Specification      | FO CA PP2-SCdx, 62,5µ, OM1, PUR, 30m                                                |
| HARTING eCatalogue | <a href="https://harting.com/33614310300006">https://harting.com/33614310300006</a> |

### Identification

|                          |                             |
|--------------------------|-----------------------------|
| Category                 | System cabling              |
| Series                   | HARTING PushPull (V4)       |
| Identification           | Industrial Fibre Optic      |
| Element                  | Cable assemblies            |
| Specification            | Pre-assembled on both sides |
| Connector 1              | HARTING PushPull (V4)       |
| Connector 2              | SC duplex                   |
| Type of cable            | FO cable                    |
| Description of the cable | Multimode<br>Overmoulded    |

### Version

|                |               |
|----------------|---------------|
| Cable length   | 30 m          |
| Core structure | 62.5 / 125 µm |

### Technical characteristics

|                                        |                |
|----------------------------------------|----------------|
| Limiting temperature                   | -40 ... +85 °C |
| Degree of protection acc. to IEC 60529 | IP68           |
| Cable diameter                         | 6.5 mm         |

### Material properties

|                         |                    |
|-------------------------|--------------------|
| Material (hood/housing) | Thermoplastic      |
| Material (cable)        | PUR (polyurethane) |



**Pushing Performance**  
 Since 1945

## Material properties

|                                      |                |
|--------------------------------------|----------------|
| RoHS                                 | compliant      |
| ELV status                           | compliant      |
| China RoHS                           | e              |
| REACH Annex XVII substances          | Not contained  |
| REACH ANNEX XIV substances           | Not contained  |
| REACH SVHC substances                | Not contained  |
| California Proposition 65 substances | Yes            |
| California Proposition 65 substances | Lead<br>Nickel |

## Specifications and approvals

|                |                                |
|----------------|--------------------------------|
| Specifications | IEC 61076-3-106 Variant 4 (V4) |
|----------------|--------------------------------|

## Commercial data

|                                |                                              |
|--------------------------------|----------------------------------------------|
| Packaging size                 | 1                                            |
| Net weight                     | 79 g                                         |
| Country of origin              | Czechia                                      |
| European customs tariff number | 85444290                                     |
| GTIN                           | 5713140272422                                |
| eCl@ss                         | 27060390 Ready-made data cable (unspecified) |
| ETIM                           | EC002599                                     |
| UNSPSC 24.0                    | 26121600                                     |