

Data sheet

770-713/007-000

PLUG SNAP IN TYPE

100% PROTECTED AGAINST MISMATING WITH DIRECT CONTACT OF THE
EARTH CONDUCTOR CAGE CLAMP S CONNECTION



Technical data

Package size 100 pieces.

pole count	3
Cross section from [mm ²]	0.5 mm ²
Cross section to [mm ²]	4 mm ²
Cross section from [AWG]	20 AWG
Cross section to [AWG]	12 AWG
Number of strands	2
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	25 A
Weight	13.155 g
Color	black
No. of connection Points	6
No. of potentials	3
Height	17.5 mm
Height	0.689 in
Width	35.5 mm
Width	1.398 in
Depth	36 mm
Depth	1.417 in
Strip length from	9 mm
Strip length to	9 mm
Strip length	0.35 in

Data sheet**770-713/007-000****PLUG SNAP IN TYPE****100% PROTECTED AGAINST MISMATING WITH DIRECT CONTACT OF THE
EARTH CONDUCTOR CAGE CLAMP S CONNECTION**

Strip length**0.35 in**

Data sheet

770-713/007-000

PLUG SNAP IN TYPE
100% PROTECTED AGAINST MISMATING WITH DIRECT CONTACT OF THE
EARTH CONDUCTOR CAGE CLAMP S CONNECTION

Approval	Voltage	Current	Approval number	Notes
CCA	250	25	NL5568	
cURus	600	20	E45171	
DNV	250	25	E6188	
GL	250	25	42875-02HH	
KEMA	250	25	2060958.03	
LR	250	20	02/20050(E1)	

Data sheet**770-713/007-000****PLUG SNAP IN TYPE
100% PROTECTED AGAINST MISMATING WITH DIRECT CONTACT OF THE
EARTH CONDUCTOR CAGE CLAMP S CONNECTION**

Accessories**Item number**

CODING FINGER FOR PLUG	770-401
LOCKOUT-CAP FOR CUTOUT	770-643
LOCKOUT-CAP FOR CUTOUT	770-693
SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 2, bar (3,5 x 0,5) mm	210-620