
Item no.: 2002-6301
Product description: 3-CONDUCTOR THROUGH TERMINAL BLOCK SUITABLE FOR EX E APPLICATIONS



Produkt kann von Bild abweichen / product may differ

Packing unit 100 pieces

RoHS compliant

Current intensity EN	32 A
Product group	22 (TOPJOB S RAIL-MOUNTED TERMINAL BLOCKS)
Cross section [mm ²]	0.25 - 2.5 mm ²
Cross section [AWG]	22 - 12 AWG
Connection method	CAGE CLAMP®S Connection
Cross section [mm ²]	0.25 - 4 mm ²
Cross section [AWG]	22 - 12 AWG
Wiring method	e+f
Connection method	CAGE CLAMP®S Connection
Measured voltage EN	800 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	24 A
Weight	5.6 g
Color	gray
Wiring type	Front-entry
No. of connection Points	3
No. of potentials	1

Height	39 mm
Height	1.535 in
Width	5.2 mm
Width	0.205 in



Depth	52 mm
Depth	2.047 in
Strip length from	10 mm
Strip length to	12 mm
Strip length	0.43 in
Customs Tariff No.	85369010
Country of Origin	China
NOTE	Ex e II approvals (pending)
Mounting	TS 35



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
2002-6301	AEX	E185892	550	20	22-12
2002-6301	CCA	NL6387	800	24/32	0,2-2,5/4
2002-6301	CSA	154112-1536069	600	20	22-12
2002-6301	GL	26187-05HH	800	24	0,25-2,5
2002-6301	KEMA	NL2116586.02	800	24	0,5-4
2002-6301	LR	91/20112(E6)	800	24	0,5-4
2002-6301	PTB	IECExPTB03.0004U	550	22	0,2-4
2002-6301	PTB	PTB03Atex1162U	550	22	0,2-4
2002-6301	RosTest	8189158	550	22	0,2-4
2002-6301	UR	E45172	600	20	22-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected