

---

Item no.: 279-995  
Product description: Ex e II double potential terminal block with double center marker receptacle SUITABLE FOR EX E APPLICATIONS

---



Produkt kann von Bild abweichen / product may differ

Packing unit 100 pieces

RoHS compliant

Product group	1 (Rail Mounted Terminal Blocks)
Cross section [mm <sup>2</sup> ]	0.2 - 1.5 mm <sup>2</sup>
Cross section [AWG]	24 - 16 AWG
Connection method	CAGE CLAMP® CONNECTION
Measured voltage EN	550 V
Current intensity EN	15 A
Weight	5.946 g
Color	light gray
Wiring type	Front-entry
No. of connection Points	4
No. of potentials	2
Height	27 mm
Height	1.06 in
Width	4 mm
Width	0.157 in
Depth	73 mm
Depth	2.87 in
Strip length from	8 mm
Strip length to	9 mm

Strip length  
Mounting

0.33 in  
TS 35



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
279-995	ABS	05-HG476175/3-PDA	800	18	1,5
279-995	AEX	E185892	352	10	28-16
279-995	BV	07436/Co	800	18	1,5
279-995	CCA	NL6098	800	18	1,5
279-995	CSA	154112-1327715	600	10	24-16
279-995	DNV	E-10423	800	18	1,5
279-995	GL	17295-00HH	800	18	1,5
279-995	GOSENERGO-Ex	99.041	550	15	1,5
279-995	KEMA	2105357.01	800	18	1,5
279-995	LR	91/20112(E6)	800	18	1,5
279-995	PRS	TE/1718/880590/08	800	18	1,5
279-995	PTB	PTB00Atex3113U	550	15	1,5
279-995	RosTest	8189158	550	15	1,5
279-995	UR	E45172	600	10	28-16

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected