



Antenna Datasheet

Product OC: YECA002L1AH

Version: 1.0

Date: 2024-09-03

Status: Released

Product Name: 4G Adhesive Mount External Monopole Antenna

Key Features:

Frequency Band: 700–960 MHz, 1710–2690 MHz

Dimensions: Φ 30 mm $\times$ 83.2 mm

Efficiency: Up to 64.5 % (MP)

RoHS and REACH Compliant

IP67

Overview

The YECA001L2AH is a 4G external antenna measuring Φ 30 mm $\times$ 83.2 mm. This ultra-wide-band 4G antenna provides broad coverage from 600–6000 MHz whilst offering backward-compatibility to support 3G and 2G networks as well as LTE Cat-M and narrowband IoT (NB-IoT). The antenna is available with connection via cable lengths from 300–5,000 mm, terminated with SMA Male (Center pin) connector. This low profile, adhesive mount omni-directional antenna, ideal for applications where the antenna is required to be discrete, is easy to install with maximum durability assured thanks to its IP67 rated and ASA enclosure. It is compatible with Quectel's 4G Series modules.

It allows constant and reliable transmission and reception due to its omni-directional gain across all frequency bands. The YECA001L2AH is designed as a monopole antenna, which offers high efficiency in all working bands. It is a perfect antenna product for customers that desire highest performance. This high-efficiency, high-gain omni-directional antenna is ideally suited for high-speed video, real-time streaming, high-capacity MIMO networks and public transportation. It is suitable for outdoor and indoor applications due to its robust UV resistant ASA enclosure, which meets UL 746C f1.

Typical applications include:

- High speed video
- Real-time streaming
- High-capacity MIMO networks
- Public transportation

Quectel provides comprehensive antenna design support such as simulation, testing and manufacturing for custom antenna solutions to meet your specific application needs. We have regional R & D centers to offer quick response to meet your requirements. Please contact our sales & FAEs if you have any requests.

Contents

Overview.....	1
Contents	2
1 Specification.....	3
1.1. Electrical.....	3
1.2. Supported Bands	5
1.3. Mechanical & Environmental	7
2 Drawing	8
3 Detailed Performance	9
3.1. S-Parameter Test	9
3.1.1. VSWR.....	9
3.1.2. Return Loss	10
3.2. Radiation Performance Test.....	11
3.2.1. Efficiency	11
3.2.2. Average Gain	12
3.2.3. Peak Gain.....	13
3.2.4. 3D & 2D Radiation Pattern.....	14
3.2.4.1. Test Condition: Free Space	14
3.2.4.2. Test Condition: On 300 mm × 300 mm Metal Plane	18
4 Packaging	22
Contact Us.....	24
Legal Notices	25
Revision History	27

1 Specification

Test Condition: Free Space & On 300 × 300 mm Metal Plane

1.1. Electrical

Electrical	
Frequency Range	700–960 MHz, 1710–2690 MHz
Impedance	50 Ω
Polarization	Linear
Radiation Pattern	Omni-directional

Electrical – Detail												
SPEC	Band	B71	B12 /B13 /B28	B5 /B8 /B26	n74 /n75 /n76	B1 /B2 /B3	B40	Wi-Fi 2G	B38 /B41	B42 /B48 /n77	n79	Wi-Fi 5G
	Freq. (MHz)	600– 700	700– 810	820– 960	1420– 1520	1700– 2170	2300– 2400	2400– 2500	2500– 2690	3300– 4200	4400– 5000	5150– 5850
Max. VSWR	FS	-	3.7	3.2	-	2.1	2.0	2.0	1.9	-	-	-
	MP	-	3.4	3.8	-	2.1	1.5	1.8	2.4	-	-	-
Max. Return Loss (dB)	FS	-	-4.9	-5.5	-	-9.0	-9.4	-9.6	-9.9	-	-	-
	MP	-	-5.2	-4.6	-	-9.0	-13.4	-10.5	-7.7	-	-	-
AVG Eff. (%)	FS	-	47.3	49.5	-	53.9	50.2	46.6	46.9	-	-	-
	MP	-	44.8	49.8	-	53.6	58.2	52.6	45.6	-	-	-
AVG AVG Gain (dB)	FS	-	-3.3	-3.1	-	-2.7	-3.0	-3.3	-3.3	-	-	-
	MP	-	-3.5	-3.0	-	-2.7	-2.4	-2.8	-3.4	-	-	-
Max. Peak Gain (dBi)	FS	-	1.7	1.3	-	4.3	3.3	3.1	2.4	-	-	-
	MP	-	1.3	2.3	-	3.7	4.4	3.2	1.9	-	-	-

VSWR	FS	≤ 3.7
	MP	≤ 3.8
Return Loss	FS	≤ -4.9 dB
	MP	≤ -4.6 dB
Peak Gain	FS	≤ 4.3 dBi
	MP	≤ 4.4 dBi

- **FS: Free Space**
- **MP: On 300 × 300 mm Metal Plane**

1.2. Supported Bands


5G NR/LTE/LTE-Advanced/WCDMA/HSPA/HSPA+/GPRS/GSM/NB-IoT					
Band	Frequency (MHz)	Uplink (MHz)	Downlink (MHz)	FS	MP
1	2100	1920–1980	2110–2170	√	√
2	1900	1850–1910	1930–1990	√	√
3	1800	1710–1785	1805–1880	√	√
4	1700	1710–1755	2110–2155	√	√
5	850	824–849	869–894	√	√
7	2600	2500–2570	2620–2690	√	√
8	900	880–915	925–960	√	√
9	1800	1749.9–1784.9	1844.9–1879.9	√	√
11	1500	1427.9–1447.9	1475.9–1495.9	-	-
12	700	699–716	729–746	√	√
13	700	777–787	746–756	√	√
14	700	788–798	758–768	√	√
17	700	704–716	734–746	√	√
18	850	815–830	860–875	√	√
19	850	830–845	875–890	√	√
20	800	832–862	791–821	√	√
21	1500	1447.9–1462.9	1495.9–1510.9	-	-
22	3500	3410–3490	3510–3590	-	-
23	2100	2000–2020	2180–2200	√	√
24	1600	1626.5–1660.5	1525–1559	-	-
25	1900	1850–1915	1930–1995	√	√
26	850	814–849	859–894	√	√

5G NR/LTE/LTE-Advanced/WCDMA/HSPA/HSPA+/GPRS/GSM/NB-IoT					
Band	Frequency (MHz)	Uplink (MHz)	Downlink (MHz)	FS	MP
28	700	703–748	758–803	√	√
31	450	452.5–457.5	462.5–467.5	-	-
34	2100	2010–2025		√	√
38	2600	2570–2620		√	√
39	1900	1880–1920		√	√
40	2300	2300–2400		√	√
41	2500	2496–2690		√	√
42	3500	3400–3600		-	-
48	3500	3550–3700		-	-
66	1700	1710–1780	2110–2200	√	√
71	600	663–698	617–652	-	-
74	1500	1427–1470	1475–1518	-	-
77	3500	3300–4200		-	-
78	3500	3300–3800		-	-
79	4500	4400–5000		-	-
Note: Covered √ means efficiency > 20 %					

1.3. Mechanical & Environmental

Mechanical		
Antenna Dimensions		Φ 30 mm × 83.2 mm
Material & Color		ASA & Black
Cable Type & Color & Length		RG174LL & Black & 1000 mm
Connector Type		SMA Male (Center pin)
Weight		Typ. 24.8 g
Mounting Type	YECA002L1AH	Adhesive
	YECM002L1AH	Magnetic
Environmental		
Operation Temperature		-40 °C to +85 °C
Storage Temperature		-40 °C to +85 °C
Ingress Protection (IP) Rating		IP67
Housing UV Resistant		UL 746C f1
RoHS and REACH Compliant		Yes

2 Drawing




Unit: mm

3 Detailed Performance

3.1. S-Parameter Test


3.1.1. VSWR



VSWR

Frequency (MHz)	600	630	710	830	900	960	1440	1710	1740	1880
FS	-	-	3.4	3.2	2.1	2.2	-	1.3	1.1	1.6
MP	-	-	2.6	3.8	2.3	2.5	-	1.3	1.2	2.0
Frequency (MHz)	1950	2140	2350	2450	2600	2690	4700	5000	5500	6000
FS	1.7	2.0	2.0	2.0	1.6	1.7	-	-	-	-
MP	2.1	1.9	1.4	1.8	2.0	2.0	-	-	-	-

3.1.2. Return Loss




Return Loss (dB)

Frequency (MHz)	600	630	710	830	900	960	1440	1710	1740	1880
FS	-	-	-5.3	-5.6	-9.2	-8.3	-	-17.4	-25.6	-13.2
MP	-	-	-7.2	-4.6	-8.0	-7.5	-	-16.8	-19.2	-9.8
Frequency (MHz)	1950	2140	2350	2450	2600	2690	4700	5000	5500	6000
FS	-11.6	-9.3	-9.4	-9.7	-12.7	-11.5	-	-	-	-
MP	-9.2	-10.4	-14.9	-10.8	-9.7	-9.5	-	-	-	-

3.2. Radiation Performance Test


3.2.1. Efficiency



Efficiency (%)

Frequency (MHz)	600	630	710	830	900	960	1440	1710	1740	1880
FS	-	-	45.3	47.0	53.3	51.3	-	60.6	61.0	51.7
MP	-	-	47.0	41.3	54.3	60.0	-	62.9	62.6	49.4
Frequency (MHz)	1950	2140	2350	2450	2600	2690	4700	5000	5500	6000
FS	50.8	46.5	52.4	45.7	48.5	44.7	-	-	-	-
MP	48.8	51.6	60.1	52.5	45.6	43.8	-	-	-	-


3.2.2. Average Gain



Average Gain (dB)

Frequency (MHz)	600	630	710	830	900	960	1440	1710	1740	1880
FS	-	-	-3.4	-3.3	-2.7	-2.9	-	-2.2	-2.1	-2.9
MP	-	-	-3.3	-3.8	-2.7	-2.2	-	-2.0	-2.0	-3.1
Frequency (MHz)	1950	2140	2350	2450	2600	2690	4700	5000	5500	6000
FS	-2.9	-3.3	-2.8	-3.4	-3.1	-3.5	-	-	-	-
MP	-3.1	-2.9	-2.2	-2.8	-3.4	-3.6	-	-	-	-

3.2.3. Peak Gain




Peak Gain (dBi)

Frequency (MHz)	600	630	710	830	900	960	1440	1710	1740	1880
FS	-	-	0.2	0.1	0.2	1.3	-	1.3	2.1	2.0
MP	-	-	1.0	-0.1	0.7	2.3	-	1.5	1.6	1.4
Frequency (MHz)	1950	2140	2350	2450	2600	2690	4700	5000	5500	6000
FS	3.2	2.9	3.2	2.4	1.4	1.2	-	-	-	-
MP	2.0	3.2	4.0	2.0	1.0	1.7	-	-	-	-

3.2.4. 3D & 2D Radiation Pattern


3.2.4.1. Test Condition: Free Space

- Test Chamber: FS-S-1




710 MHz

MAX: 0.24dBi
MIN: -28.38dBi




Theta=90 Freq=710MHz




830 MHz


MAX: 0.06dBi
MIN: -19.37dBi




Theta=90 Freq=830MHz




Phi=0 Freq=710MHz




Phi=90 Freq=710MHz



Phi=0 Freq=830MHz




Phi=90 Freq=830MHz




900 MHz

MAX: 0.18dBi
MIN: -15.37dBi




Theta=90 Freq=900MHz




1740 MHz


MAX: 2.05dBi
MIN: -28.57dBi




Theta=90 Freq=1740MHz




Phi=0 Freq=900MHz




Phi=90 Freq=900MHz




Phi=0 Freq=1740MHz




Phi=90 Freq=1740MHz






2450 MHz

MAX: 2.38dBi
MIN: -30.84dBi




Theta=90 Freq=2450MHz




2600 MHz


MAX: 1.44dBi
MIN: -20.52dBi




Theta=90 Freq=2600MHz




Phi=0 Freq=2450MHz




Phi=90 Freq=2450MHz



Phi=0 Freq=2600MHz




Phi=90 Freq=2600MHz




3.2.4.2. Test Condition: On 300 mm × 300 mm Metal Plane

- Test Chamber: FS-S-1




710 MHz

MAX:0.98dBi
MIN:-25.1dBi




Theta=90 Freq=710MHz




830MHz


MAX:-0.05dBi
MIN:-23.77dBi




Theta=90 Freq=830MHz




Phi=0 Freq=710MHz




Phi=90 Freq=710MHz



Phi=0 Freq=830MHz




Phi=90 Freq=830MHz




900 MHz

MAX:0.74dBi
MIN:-20.69dBi




Theta=90 Freq=900MHz




1740 MHz


MAX:1.59dBi
MIN:-27.48dBi




Theta=90 Freq=1740MHz




Phi=0 Freq=900MHz




Phi=90 Freq=900MHz



Phi=0 Freq=1740MHz




Phi=90 Freq=1740MHz




1880 MHz

MAX:1.38dBi
MIN:-19.98dBi




Theta=90 Freq=1880MHz




1950 MHz


MAX:1.95dBi
MIN:-26.47dBi




Theta=90 Freq=1950MHz




Phi=0 Freq=1880MHz




Phi=90 Freq=1880MHz



Phi=0 Freq=1950MHz




Phi=90 Freq=1950MHz




2140 MHz

MAX:3.23dBi
MIN:-22.26dBi




Theta=90 Freq=2140MHz




2350 MHz


MAX:4dBi
MIN:-36.09dBi




Theta=90 Freq=2350MHz




Phi=0 Freq=2140MHz




Phi=90 Freq=2140MHz



Phi=0 Freq=2350MHz




Phi=90 Freq=2350MHz




2450 MHz

MAX:2.01dBi
MIN:-35.52dBi




Theta=90 Freq=2450MHz




2600 MHz


MAX:1.04dBi
MIN:-33.03dBi




Theta=90 Freq=2600MHz




Phi=0 Freq=2450MHz




Phi=90 Freq=2450MHz






Phi=0 Freq=2600MHz





Phi=90 Freq=2600MHz



4 Packaging

Step	Packaging Picture / 2D Picture	Description
1		1 pc antenna product in a small PE bag. (1 PC Antenna / Small PE Bag)
2		40 pcs antenna products in a big PE bag. (40 PCS Antennas / Big PE Bag)
3		(4 PE Bags / Carton Box) (160 PCS Antennas / Carton Box) Estimated quantity Products that cannot fill the entire carton box are packed in a suitable size carton box. <u>Carton Size:</u> <u>L × W × H = 370 × 370 × 295 mm</u>

4		Position for Attaching Labels ① Carton Label ② Quality Label
5		Sealing Cartons “I” type sealing cartons
6	The initial packaging method described above is for reference only, and the final actual packaging method shall be subject to the actual shipping packaging.	

Contact Us

At Quectel, our aim is to provide timely and comprehensive services to our customers. If you require any assistance, please contact our headquarters:

Quectel Wireless Solutions Co., Ltd.

Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai 200233, China

Tel: +86 21 5108 6236

Email: info@quectel.com

Or our local offices. For more information, please visit:

<http://www.quectel.com/support/sales.htm>.

For technical support, or to report documentation errors, please visit:

<http://www.quectel.com/support/technical.htm>.

Or email us at: support@quectel.com.

Legal Notices

We offer information as a service to you. The provided information is based on your requirements and we make every effort to ensure its quality. You agree that you are responsible for using independent analysis and evaluation in designing intended products, and we provide reference designs for illustrative purposes only. Before using any hardware, software or service guided by this document, please read this notice carefully. Even though we employ commercially reasonable efforts to provide the best possible experience, you hereby acknowledge and agree that this document and related services hereunder are provided to you on an “as available” basis. We may revise or restate this document from time to time at our sole discretion without any prior notice to you.

Use and Disclosure Restrictions

License Agreements

Documents and information provided by us shall be kept confidential, unless specific permission is granted. They shall not be accessed or used for any purpose except as expressly provided herein.

Copyright

Our and third-party products hereunder may contain copyrighted material. Such copyrighted material shall not be copied, reproduced, distributed, merged, published, translated, or modified without prior written consent. We and the third party have exclusive rights over copyrighted material. No license shall be granted or conveyed under any patents, copyrights, trademarks, or service mark rights. To avoid ambiguities, purchasing in any form cannot be deemed as granting a license other than the normal non-exclusive, royalty-free license to use the material. We reserve the right to take legal action for noncompliance with abovementioned requirements, unauthorized use, or other illegal or malicious use of the material.

Trademarks

Except as otherwise set forth herein, nothing in this document shall be construed as conferring any rights to use any trademark, trade name or name, abbreviation, or counterfeit product thereof owned by Quectel or any third party in advertising, publicity, or other aspects.

Third-Party Rights

This document may refer to hardware, software and/or documentation owned by one or more third parties (“third-party materials”). Use of such third-party materials shall be governed by all restrictions and obligations applicable thereto.

We make no warranty or representation, either express or implied, regarding the third-party materials, including but not limited to any implied or statutory, warranties of merchantability or fitness for a particular purpose, quiet enjoyment, system integration, information accuracy, and non-infringement of any third-party intellectual property rights with regard to the licensed technology or use thereof. Nothing herein constitutes a representation or warranty by us to either develop, enhance, modify, distribute, market, sell, offer for sale, or otherwise maintain production of any our products or any other hardware, software, device, tool, information, or product. We moreover disclaim any and all warranties arising from the course of dealing or usage of trade.

Privacy Policy

To implement module functionality, certain device data are uploaded to Quectel's or third-party's servers, including carriers, chipset suppliers or customer-designated servers. Quectel, strictly abiding by the relevant laws and regulations, shall retain, use, disclose or otherwise process relevant data for the purpose of performing the service only or as permitted by applicable laws. Before data interaction with third parties, please be informed of their privacy and data security policy.

Disclaimer

- a) We acknowledge no liability for any injury or damage arising from the reliance upon the information.
- b) We shall bear no liability resulting from any inaccuracies or omissions, or from the use of the information contained herein.
- c) While we have made every effort to ensure that the functions and features under development are free from errors, it is possible that they could contain errors, inaccuracies, and omissions. Unless otherwise provided by valid agreement, we make no warranties of any kind, either implied or express, and exclude all liability for any loss or damage suffered in connection with the use of features and functions under development, to the maximum extent permitted by law, regardless of whether such loss or damage may have been foreseeable.
- d) We are not responsible for the accessibility, safety, accuracy, availability, legality, or completeness of information, advertising, commercial offers, products, services, and materials on third-party websites and third-party resources.

Copyright © Quectel Wireless Solutions Co., Ltd. 2024. All rights reserved.

Revision History

Version	Date	Author	Note
-	2024-08-31	Mordecai LIU/ Jason LONG/ David LIU/ Rainey LIAO	Creation of the document
1.0	2024-08-31	Mordecai LIU/ Jason LONG/ David LIU/ Rainey LIAO	First official release



www.quectel.com