



CRC Brākleen Pro

1. General Description

Brake parts cleaner with a formulation based on multiple active ingredients for effective removal of oil, grease, traffic dirt and brake fluid. Highly effective. pleasant odour and handy 360° spray system. Fast drying, zero residue.

2. Characteristics

- Effectively removes brake fluid, grease, oil and hardened deposits.
- Reduces disc-brake squeal and clutch chatter.
- Fast evaporation to minimize downtime.
- Does not leave a residue.
- Safe on all metal surfaces, does not stain.
- Safe on most rubbers, plastics and coatings.
- Test on sensitive or stressed materials before use.
- Convenient 360° (including inverted position) spray valve
- High purity CO2 propellant, giving an active product content of 95%.

3. Applications

- Perfect for cleaning and degreasing of all brake and clutch parts.
- General cleaning of mechanical parts.

4. Instructions

- Spray liberally and allow to run off.
- Allow to dry at ambient temperature.
- Repeat if necessary.
- Test before use on sensitive materials.
- Do not use on energized equipment.
- Do not use on sensitive electronic equipment.
- Do not reactivate equipment until treated components are completely dry & free from product.
- Ensure adequate ventilation.
- Protect and re-lubricate if necessary.

A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.



CRC Bräkleen Pro

5. Typical Product Data (without propellant)

• Appearance	:	Liquid.
• Colour	:	Clear.
• Odour	:	Citrus.
• Density	:	0.712 g/cm ³ (@ 20°C).
• Flash Point	:	< 0 °C
• Auto Ignition temperature	:	> 200 °C
• Evaporation rate	:	2.8 (Ether=1)
• Vapor density	:	3 (@ 20°C).
• Surface tension active product	:	21 mN/m

6. Remarks

Sensitive plastics (e.g. polystyrenes and polycarbonates) need to be checked, particularly when thermal or mechanical stress is involved.

7. Packaging

Aerosol: 12x500 ML

Bulk: 5L , 20L , 60L , 200L

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website:

www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Date: 09/04/2023