

Electronic housing - BC 161,6 OT 000C0C22 KMGY - 2201678

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Installation component housing, Upper part, Color: light gray, Width: 161.6 mm, Constructional height: 62.2 mm

Why buy this product

- Item is from the BC product range
- Conforms to DIN EN 43880
- Tool-free mounting
- Available in overall widths from one to nine width units (17.8 mm ... 161.6 mm)
- Inflammability class V0 according to UL 94
- Variety of connection technologies
- Can be mounted on the DIN rail or the wall
- Optional with bus connector for DIN rail mounting

Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	 4 046356 906630
GTIN	4046356906630
Weight per Piece (excluding packing)	65.150 g
Custom tariff number	85472000
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

General

Housing type	Installation component housing
Housing material	Polycarbonate
Color	light gray

Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
---------------------------------	----------------------------------------------------

Dimensions

Electronic housing - BC 161,6 OT 000C0C22 KMGY - 2201678

Technical data

Dimensions

Length	89.7 mm
Constructional height	62.2 mm
Width	161.6 mm

Technical data

Flammability rating according to UL 94	V0
Power dissipation without gap	16.95 W

Standards and Regulations

Flammability rating according to UL 94	V0
----------------------------------------	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values