



TAPE AND REEL SPECIFICATIONS:

FEED DIRECTION

1 TAPE:

REEL DIA. REF.

> .500 [12.7] DIA. HOLE THRU

±.005 [±0.15]

WIDTH

MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER ANSI/EIA-481 STANDARD

FEED DIRECTION

±.005 [±0.15]

0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0

- PITCH

 $\pm .005 [\pm 0.15]$

±.005 [±0.15]

.457 [11.60] —

.059 [1.5] DIA.

HOLE (TYP.)

.157 [4.0]

.945 [24.0] WIDE; .473 [12.00] PITCH

DESCRIPTION

2. REEL:

DATE

13.0 [330.2] DIA. 1500 PIECES OF PART NO. 3050 PER REEL.

	KEYSTONE ELECTRONICS CORP.			
	www.keyelco.com • ASTORIA, N.Y. 11105-2017 • Tel (718) 956-8900			
	PART NAME SM RETAINER ON TAPE			
	MATERIAL			
	AS NOTED			
	FINISH AS NOTED		DRN BY NT	12.30.10
	AS NOTED		APP'D LN	SCALE X
	TOLERANCES INCH [MM]	CODE	DWG NO.	
REV.	DECIMAL ± .015 [± 0.38] ANGULAR ± 1° UNLESS OTHERWISE SPECIFIED	C/M	3050TR	