


Item no.: 734-234
 Product description: Male header (for PCBs) Straight solder pin 1 x 1 mm 4-pole Pin spacing 3.81 mm / 0.15 in 100% protected against mismatching with closed end Vertical PCB mounting



Produkt kann von Bild abweichen / product may differ

Packing unit 200 pieces

RoHS compliant

Product group	3 (Multi Conn. System)
Weight	1.063 g
Color	orange
pole count	4
Height	10.3 mm
Height	0.406 in
Width	17.33 mm
Width	0.682 in
Depth	8.5 mm
Depth	0.335 in
Pin spacing from	3.81 mm
Pin spacing from	0.15 in
Rating based on	IEC/EN 60664-1
Overvoltage category EN I	III
Pollution degree	2
Measured voltage EN	160 V
Measured shock voltage	2.5 kV
Current intensity EN	10 A

Overvoltage category EN II	II
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	2.5 kV



Current intensity EN	10 A
Overvoltage category EN III	III
Degree of pollution	3
Rated voltage EN	160 V
Rated surge voltage	2.5 kV
Nominal current	10 A
Solder pin length [mm]	4.5 mm
Solder pin width A [mm]	1 mm
Solder pin width B [mm]	1 mm
Diameter of drilled hole [mm]	1.4 mm
Tolerance of drilled hole diameter [mm]	0.1 mm
Material group	I
Insulating material	PA 6.6
Temperature stability	-60 °C to +100 °C
Flammability category, based on UL 94	V0
Contact material	Electrolytic copper (Ecu)
Contact plating	tin-plated



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
734-234	ABS	04-HG469925/1-PDA	250	10	0,5-1,5
734-234	BV	11915/A0	250	10	0,5-1,5
734-234	CCA	NL5641	250	10	0,5-1,5
734-234	CSA	154112-1465035	300	10	28-14
734-234	DNV	E-9218	250	10	0,5-1,5
734-234	GL	17296-00HH	250	10	0,5-1,5
734-234	KEMA	2077592.02	250	10	0,5-1,5
734-234	LR	96/20035	250	10	0,5-1,5
734-234	RMR	11130002	250	10	0,5-1,5
734-234	UR	E45171	250	10	28-14
734-234	UR	E45172	300	10	

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected