EPIC® MC Module: HE 4pole

05.11.2015

The mixed assembly guarantees high flexibility. For applications in mechanical and plant engineering, for printing machines and slide-in technology.

The mix of different functions in one plug guarantees high flexibility Assembly of individual connectors, suitable for different applications



Automation



Industrial machinery and plant engineering



Wind Energy

Application range

Plant engineering Printing machines Control engineering

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data Rated voltage (V):	630 V
0 ()	
Rated current (A):	25 A
Contact resistance:	< 2 mOhm
Contacts:	Copper alloy, hard silver-plated
Number of contacts:	4
Termination methods:	Crimp termination: 0.5 - 4.0 mm ²
Cycle of mechanical operation:	100
Temperature range:	-40°C to +100°C, short-term up to +125°C
Degree of soiling:	3

		[
Product Management	Document: LAPP_PRO813EN.pdf	1/3
PN 0486/01_03.10 ©2012 Lapp Group - Technical changes reserved Photographs are not to scale and do not represent detailed images of the respective products.		

	Part number	Article description	Contact type	Number of operating contacts	Slots	Pieces / PU
Module: 4-pin HE						
	10399000	MCS 4 CM	male	4	1	10
	10399100	MCB 4 CM	female	4	1	10

U.I. Lapp GmbH

PRODUCT INFORMATION

® LAPP GROUP

EPIC® MC Module: HE 4pole

05.11.2015

Product Management

Document: LAPP_PRO813EN.pdf


N	
ω	

U.I. Lapp GmbH	PRODUCT INFORMATION

EPIC® MC Module: HE 4pole

05.11.2015





Product Management	Document: LAPP_PRO813EN.pdf	3 / 3
PN 0486/01_03.10 ©2012 Lapp Group - Technical changes reserved Photographs are not to scale and do not represent detailed images of the respective products.		