



PCN / EOL Notification

PCN Number: CC144901B (Revised 3/17/16) Notification Date*: December 18, 2014
See Changes in Blue Text

Title: AT24C32D to AT24C32E — 32-Kbit I2C-Compatible (Two Wire Interface) Industrial Temperature Grade (-40°C to 85°C) Serial EEPROM Process Optimization and Device Enhancement Note: Continued Support of 5V 1-Kbit Two-Wire Interface Industrial Temperature Grade (-40 to 85C) EEPROM device (AT24C32D)		
Product Identification: AT24C32D (1.7 to 5.5V); AT24C32E (1.7 to 3.6V): All Packages Industrial Temp. Grade (-40C to +85C)		
Reason for Change:	<input type="checkbox"/> Material / Composition <input type="checkbox"/> Processing / Manufacturing <input checked="" type="checkbox"/> Design / Firmware <input checked="" type="checkbox"/> Datasheet	<input type="checkbox"/> Manufacturing Location <input type="checkbox"/> Quality / Reliability <input type="checkbox"/> Logistics <input type="checkbox"/> Other:
Change Description: Atmel launched a new low voltage (1.7V- 3.6V) variant of the I2C 2-Kbit EEPROM Industrial Grade (-40C to +85C) device AT24C32E in 2014. The new, low voltage device has significant improvements and advantages over the existing wide voltage (1.7V – 5.5V) device AT24C32D with respect to power consumption, endurance, and noise suppression. With a growing number of MCUs, SoCs, and ASICs migrating to lower supply voltages as a result of process lithography reductions, and to reduce power consumption, Atmel developed the AT24C32E to specifically work with a 1.7V to 3.6V supply. However Atmel recognizes that some applications might still require a 5V supply voltage, so this addendum to the PCN is to confirm that Atmel will continue to support and produce the wide voltage device AT24C32D. Therefore, customers may continue with the AT24C32D in all applications that use 5V or 3.3V supply voltage. However, for applications tailored towards low voltage operation (e.g. 1.8V, 3.0V, etc.), Atmel recommends customers migrate to the enhanced performance of the AT24C32E. (See table below for details of AT24C32E's low voltage enhancements.)		

Table 1

Parameter/Feature	AT24C32D	AT24C32E
Operating Voltage	1.7V to 5.5V	1.7V to 3.6V
Operating Temperature	-40°C to +85°C	-40°C to +85°C
Endurance	1,000,000 cycles (Page Mode, +25°C, 3.3V)	1,000,000 cycles (Byte or Page Mode, +25°C, 1.7V to 3.6V)
Data Retention	100 years	100 years
Supply Current, Read	0.4mA typ (5.0V, 100kHz) 1.0mA max (5.0V, 100kHz)	0.08mA typ (1.8V, 400kHz) 0.3mA max (1.8V, 400kHz) 0.15mA typ (3.6V, 1MHz) 0.5mA max (3.6V, 1MHz)
Supply Current, Write	2.0mA typ (5.0V, 100kHz) 3.0mA max (5.0V, 100kHz)	0.2mA typ (3.6V, 1MHz) 1.0mA max (3.6V, 1MHz)
Standby Current	1.0µA max (1.7V) 6.0µA max (5.0V)	0.08µA typ (1.8V) 0.4µA max (1.8V) 0.1µA typ (3.6V) 0.8µA max (3.6V)
Maximum Clock Frequency	1MHz (2.5V min.) 400kHz (1.7V min.)	1MHz (2.5V min.) 400kHz (1.7V min.)
Clock Pulse Width Low	1.3µs min (f _{SCL} = 400kHz) 0.4µs min (f _{SCL} = 1MHz)	1.3µs min (f _{SCL} = 400kHz) 0.5µs min (f _{SCL} = 1MHz)
Clock Pulse Width High	0.6µs min (f _{SCL} = 400kHz) 0.4µs min (f _{SCL} = 1MHz)	0.6µs min (f _{SCL} = 400kHz) 0.4µs min (f _{SCL} = 1MHz)
Input Filter Noise Suppression	100ns max (f _{SCL} = 400kHz) 50ns max (f _{SCL} = 1MHz)	100ns max (f _{SCL} = 400kHz) 100ns max (f _{SCL} = 1MHz)
Clock Low to Data Out Valid	900ns max (f _{SCL} = 400kHz) 550ns max (f _{SCL} = 1MHz)	900ns max (f _{SCL} = 400kHz) 450ns max (f _{SCL} = 1MHz)
Bus Free Time Between Start and Stop	1.2µs min (f _{SCL} = 400kHz) 0.5µs min (f _{SCL} = 1MHz)	1.3µs min (f _{SCL} = 400kHz) 0.5µs min (f _{SCL} = 1MHz)
Input Rise Time	300ns max (f _{SCL} = 400kHz) 300ns max (f _{SCL} = 1MHz)	300ns max (f _{SCL} = 400kHz) 100ns max (f _{SCL} = 1MHz)
Input Fall Time	300ns max (f _{SCL} = 400kHz) 100ns max (f _{SCL} = 1MHz)	300ns max (f _{SCL} = 400kHz) 100ns max (f _{SCL} = 1MHz)
Write Cycle Time	5ms max	5ms max
Page Write Size	32 bytes max	32 bytes max
Full Array Hardware Write Protect	Yes	Yes

Identification Method to Distinguish Change:

Different catalog part numbers for AT24C32D and AT24C32E exist. Please refer to the respective datasheets for part marking schemes for each package type.

Table 2

Below is a part number cross reference for the AT24C32D and AT24C32E families. Special CAN (customer specific) part numbers created for the AT24C23D that are not listed in the table below remain in production:

5.5V Part Number	3.6V Part Number	Package	Carrier Type
AT24C32D-PUM	AT24C32E-PUM	PDIP	Bulk
AT24C32D-SSHM-B	AT24C32E-SSHM-B	SOIC	Bulk
AT24C32D-SSHM-T	AT24C32E-SSHM-T	SOIC	Tape & Reel (4K/reel)
AT24C32D-XHM-B	AT24C32E-XHM-B	TSSOP	Bulk
AT24C32D-XHM-T	AT24C32E-XHM-T	TSSOP	Tape & Reel (5K/reel)
AT24C32D-MAHM-T	AT24C32E-MAHM-T	UDFN	Tape & Reel (5K/reel)
AT24C32D-MAHM-E	AT24C32E-MAHM-E	UDFN	Tape & Reel (15K/reel)
AT24C32D-MEHM-T	none ⁽¹⁾	XDFN	Tape & Reel (5K/reel)
AT24C32D-STUM-T	AT24C32E-STUM-T	SOT23	Tape & Reel (5K/reel)
AT24C32D-UUM-T	AT24C32E-UUM0B-T ⁽²⁾	WLCSP	Tape & Reel (5K/reel)
AT24C32D-CUM-T	AT24C32E-CUM-T	VFBGA	Tape & Reel (5K/reel)
AT24C32D-WWU11M	AT24C32E-WWU11M	Wafer Sales	n/a

Note 1: The 1.8x2.2mm XDFN package is not offered on the AT24C32E.

Note 2: The WLCSP 5-ball grid pattern used on the AT24C32D does not fit the new AT24C32E. A new 5-ball WLCSP is offered its place. The new device includes a backside coating to increase product robustness.

Qualification Data:	<input checked="" type="checkbox"/> Available	<input type="checkbox"/> Will be available (mm/dd/yr):	<input type="checkbox"/> Not Applicable
Samples:	<input checked="" type="checkbox"/> Available Now. Please contact Atmel Sales to submit Sample Request Form (samples in tape format only)	<input type="checkbox"/> Will be available (mm/dd/yr):	<input type="checkbox"/> Not Applicable

Quantifiable Impact on Quality & Reliability:

AT24C32E is form, fit, and function of AT24C32D for 1.7 to 3.6V.

Forecasted Availability Date: AT24C32D - already available
 AT24C32E - already available

Last Time Buy Date: ~~June 18, 2015~~

Last Ship Date: ~~December 18, 2015~~

**All orders placed after the notification date are non-cancellable and non-returnable (NCNR).*

Atmel Contact: Please contact your Atmel Sales Representative or Distributor for additional information (when replying via e-mail please include the PCN number in subject line).

Information provided herein is in connection with Atmel products and this information is provided "AS IS". Atmel assumes no responsibility for any errors that may appear in this document. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Atmel's Terms and Conditions of Sale for such products, Atmel assumes no liability whatsoever, and Atmel disclaims any express or implied warranty, including liability or warranties relating to fitness for a particular purpose, merchantability, or non-infringement of any patent, copyright or other intellectual property right. Atmel products are not intended for use in a product or system intended to support or sustain life which, if it fails, can be reasonably expected to result in significant personal injury. Atmel may make changes to specifications and product descriptions at any time, without notice.

Attention Distributors: Product(s) identified in this notification will become obsolete and as such this EOL notification will act as the official written notification. All obsolete products will be listed in the next published quarterly distributor price book, following an PCN/EOL change, and listed on the obsolescence form which accompanies said price book. Within thirty (30) days from the published date of the price book, Distributor shall notify Atmel in writing of Distributor's then current inventory of the obsolete product

CUSTOMER ACKNOWLEDGEMENT OF RECEIPT: Atmel requests you acknowledge receipt of this PCN / EOL. Please complete and email to pcnadm@atmel.com and the Atmel Contact listed above. In your acknowledgement, you can grant approval or request additional information. **Atmel will deem this change accepted unless specific conditions of acceptance are provided in writing within 30 days from the date of this notice.**

To be completed by customer:

Approved

Rejected (Please state reason for rejection): _____

Company:
 Name:
 Title:
 Date:
 Email
 Address:
 Location:
 Comments: