

Item no.: 250-410
 Product description: 1-CONDUCTOR PCB TERMINAL STRIP 1 SOLDER PIN /
 POLE STAGGERED 10 POLE PIN SPACING 2.5 MM / 0.098
 IN WITH PUSH BUTTONS WITH TEST SLOT FOR TEST
 PLUG TO 1.3 MM Ø



Produkt kann von Bild abweichen / product may differ

Packing unit 1 piece

RoHS compliant

Product group	4 (Printed Circuit)
Weight	3.63 g
Color	gray
No. of connection Points	10
No. of potentials	10
pole count	10
Height	13.1 mm
Height	0.516 in
Width	26.5 mm
Width	1.043 in
Depth	12 mm
Depth	0.472 in
Pin spacing from	2.5 mm
Pin spacing from	0.098 in
Pollution degree	2
Measured voltage EN	160 V
Measured shock voltage	2.5 kV

Current intensity EN	4 A
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	2.5 kV
Current intensity EN	4 A



Diameter from	0.4 mm
Diameter to	0.8 mm
Cross section [mm ²]	0.14 - 0.5 mm ²
Wiring method	solid
Cross section [mm ²]	0.2 - 0.5 mm ²
Wiring method	fine-stranded
Cross section to [mm ²]	0.25 mm ²
Wiring method	fine-stranded (with ferrule and plastic collar)
Cross section to [mm ²]	0.25 mm ²
Wiring method	fine-stranded (with ferrule, without plastic collar)
Cross section [AWG]	24 - 20 AWG
Strip length from	8.5 mm
Strip length to	9.5 mm
Material group	I
Contact surface	Copper
xxx-xxx/000-004	black
xxx-xxx/000-005	red
xxx-xxx/000-006	blue
xxx-xxx/000-009	light gray
xxx-xxx/000-012	orange
xxx-xxx/000-024	violet
xxx-xxx/000-050	white



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
250-410	CCA	NL6336	250	6	0,2-1,5
250-410	CSA	154112-1132097	300	2	24-22
250-410	KEMA	2114919.01	250	6	0,2-1,5
250-410	UR	E45172	300	5	26-20

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected