



Pushing Performance
Since 1945

HA PPV4 2.0 RJ45 Cat6A PVC outd. 1,0m



Image is for illustration purposes only. Please refer to product description.

Part number	09 48 282 8758 010
Specification	HA PPV4 2.0 RJ45 Cat6A PVC outd. 1,0m
HARTING eCatalogue	https://harting.com/09482828758010

Identification

Category	System cabling
Series	HARTING PushPull (V4)
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	HARTING PushPull (V4) RJ45
Connector 2	HARTING PushPull (V4) RJ45
Type of cable	Copper cable (round)
Description of the cable	Wiring 1:1

Version

Cable length	1 m
Number of cores	8
Core structure	4x 2x AWG 26/7
Shielding	Shielded

Technical characteristics

Transmission characteristics	Cat. 6 _A Class E _A up to 500 MHz
Data rate	10 Mbit/s
	100 Mbit/s
	1 Gbit/s
	2.5 Gbit/s
	5 Gbit/s
	10 Gbit/s



Pushing Performance
Since 1945

Technical characteristics

Limiting temperature	-20 ... +70 °C
Degree of protection acc. to IEC 60529	IP65 / IP67

Material properties

Material (cable)	PVC
Colour (cable)	Black
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

Specifications and approvals

Specifications	IEC 61076-3-106 Variant 4 (V4)
----------------	--------------------------------

Commercial data

Packaging size	1
Net weight	96.58 g
Country of origin	Latvia
European customs tariff number	85444290
GTIN	5713140246034
eCl@ss	27060390 Ready-made data cable (unspecified)
ETIM	EC002599
UNSPSC 24.0	26121600